COMMONSENSE
EPOS LTD

TE8500

A stylish Casio net workable EPOS terminal suitable for restaurants, pubs, cafes and fast food businesses

TE8500 Hospitality EPOS for fast, accurate registration

Large, tilting, operator display with 5 colour backlight

Terminals can be networked for consolidated sales data

Compact flash interface for data back-up

System Features

The TE8500 is an ideal net workable solution for stock and management control in a busy environment. Pre-set menu items and drop down menus enable staff to register sales quickly and accurately and each terminal has 4 x RS232c ports for PC direct connection/back office, external printers, slip printer and/or remote customer display. Multiple terminals can be networked in order to share operations and to consolidate sales data. The TE8500 has fast, silent, thermal built in printers for both receipt (with auto cutter) and journal record. A 5.2" LCD operator display enables a clear view of all transaction information. There is a 5 colour backlight with a scheduler function which allows switching between backlight colour and menu level to differentiate items or prices (i.e. between lunch & dinnertime menus) . There is drop-in till roll loading for easy handling.
. Key features include clerk interrupt (Lay-away) or table tracking and a comprehensive range of management reports, with the ability to send orders to a kitchen printer.

ℝ eports

- Financial
- Transaction
- Department, sub-dept. PLU
- Table analysis
- Open Check
- Monthly
- Hourly, hourly item
- Employee
- (time & attendance)
- Flash
- Group
- Clerk
- Scanning PLU
- Mix & Match
- Not-found PLU

𝕊 pecification

- Operator display - 5.2" LCD with colour backlight. 2 x 16 characters/10 digits, 7 segments
- Customer - Pop-up 10 digit numeric LED
- Printing - two-station thermal printer with receipt auto cutter.
- Memory backup - 90 day (vanadium lithium battery)
- Power - AC 120V (operating 0.9A, standby 0.2A) - AC 230V (operating 0.5A, standby 0.11A)
- Op. environment: Temp: 0 to 40C Humidity:10 to 85% RH
- Dimension (WDH): 410x491x215 (292)mm
- Weight: approx 9kg